

# Cat<sup>®</sup> Ultra Synthetic Generator Grease



## Long Life, Extreme Pressure

Cat<sup>®</sup> Ultra Synthetic Generator Grease is a non-soap lubricating grease formulated in a synthetic hydrocarbon base fluid which provides extremely low cold-temperature start-up and running performance. Cat Ultra Synthetic Generator Grease contains extreme pressure and anti-wear additives and provides long service life due to excellent oxidation stability.



# Cat® Ultra Synthetic Generator Grease

Typical Characteristics	
Color	Red
Appearance	Smooth
Thickener Type	Organophilic Clay
Penetration, Worked 60, ASTM D 217	285-315
Dropping Point, ASTM D 2265	>500
4 Ball Load Weld Load	200
4 Ball Wear Scar (mm) (base product)	0.70
Corrosion Resistance	Pass
Base Oil Viscosity @ 40° C @ 100° C	6 cSt 31 cSt
Viscosity Index	135
Pour Point ° C	-60
Flash Point ° C	225



## Benefits:

- NLGI #1.5
- Formulated with an Organo-Clay thickener and a synthetic base oil
- Not recommended for applications requiring the Caterpillar T-4 specification
- \* Excellent high and low temperature performance
- \* For operating temp ranges of -50°C to 180°C (-58°F to 356°F)

## CAT DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts can help you maximize your equipment investment.



PEHJ0332-00  
www.cat.com

© 2013 Caterpillar • All Rights Reserved • Printed in USA  
CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow", the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

