

**POWERTRAIN**

CAT C4.4 Tier 4 engine, 137 HP  
High-torque, direct drive motor

**OPERATING ENVIRONMENT**

Dual side operating controls available  
Adjustable speed chain control w/ reverse  
Variable speed drive system  
Manual hydraulic valves keep system simple

**MATERIAL DELIVERY**

58" by 7" deep conveyor slats  
3 independent, adjustable scrapers  
121" conveyor throat width  
84" discharge height  
60" wide conveyor with 1,400/tph capacity

**PAVER HOOKUP**

Sliding hitch for paver hookup  
Swing-up towing frame  
Hydraulic pin push frame option

**OPTIONAL REMIXING DISCHARGE HOPPER**

Provides consistent mix of material to paver  
Hydraulically moves into position

**OPTIONAL TRANSPORT AXLE**

Heavy-duty 20,000 pound axle  
Hydraulic lift cylinders  
Hydraulic towing frame  
Quickly pins on/off elevator

**SERVICE**

Instrument panel gauges  
Hinged access doors  
Face-sealed hoses and fittings  
Easily accessible battery compartment  
Vandal covers  
Braided electrical harnesses and sealed connections  
Color-coded electrical wires

**OPTIONAL EQUIPMENT**

Transport Axle Group  
Hydraulic Pin Push Frame  
Remixing Discharge Hopper  
Ni-Hard Floor Plates  
Spray Down for Chains and Sprockets  
LED Lighting Group  
Opposite Side Hydraulics Control

**WARRANTY**

12 months

**SALES AND SERVICE**

Sold and serviced exclusively through CAT dealers worldwide

**SPECS**

Weight: 18,000 lb  
Height: 124"  
Length: 205"  
Length w/ Raised Towing Frame: 163"  
Width w/ Wings In; 102"  
Width w/ Wings Out: 125"  
Engine Cat C4.4 Tier 4  
Horsepower: 137 hp  
Conveyor Throat Width: 121"  
Conveyor Slat Width: 58"  
Conveyor Slat Depth: 7"  
Discharge Height: 84"  
Front Wheel Cylinder Lift: 8"  
Front Tire Size: 16" x7"  
Rear Tire Size: 8.25 x R15  
Fuel Tank Capacity: 80 gal  
Hydraulic Tank Capacity: 40 gal



## MATERIAL DELIVERY

- High-slat entry tackles tall windrows
- 118" wide throat, with 29" augers, delivers high production
- Three-point suspension consisting of hydraulic cylinder for each front wheel and interconnected cylinders for the rear wheels ensure a secure bond between mat and tack coat
- 60" wide conveyor with 1,400 ton-per-hour capacity
- Conveyor powered by high-torque, direct-drive motor which eliminates a gearbox and is kept cool by a loop flush return system



## CONTROLS

- Electronic controller provides machine conditions, diagnostics and calibrations
- Easy-access chain speed and direction control
- Operating controls located on both sides of the machine protect the operator by offering a choice to work on either side of the machine
- Variable hydraulic drive system allows speed of the conveyor to match material and production requirements



## REMIXING DISCHARGE HOPPER

- Provides consistent material mix to the paver
- Hydraulically moves into and out of position
- Independent doors control material flow



## TRANSPORT AXLE

- Axle rated at 20,000 lbs.
- Quickly pins on/off elevator
- Hydraulic tongue for easy tow vehicle hookup
- Axle alone moveable with skid steer, loader bucket or pintle hitch



## SERVICE AND SUPPORT

- Cat Dealer sales, service and support
- Electronic controller provides machine conditions, diagnostics and calibrations
- Face-sealed hoses and fittings provide increased reliability and serviceability
- Two large access doors and platforms allow easy access to the engine compartment